

TECHNICAL DATA SHEET **LEFT-LUGGAGE LOCKERS**

CAS 400 SERIES













CHARACTERISTICS

Welded Monoblok locker boxes, manufactured with cold laminated sheet metal DC01, according to the European Norm EN 10130, with a carbon content of less than 0,12%.

Metal thickness of 0.8mm.

Point welding process.

Previous treatment of passivating and degreasing.

Dried in a polymerization oven at 180°C during 15 minutes.

Painting with Epoxy-polyester powder in robotized cabins.

Body and doors painted in grey RAL 7035 Micro-textured finish. Minimum thickness of the painting: 50 microns.

Chromed standard cylinder locks with two keys per lock or cain-operated lock with coin-return.

Screws and nuts to join the locker boxes together with each other included.

Monoblok construction.

Stackable. Can be joined together to form sets.



CAS431



CAS432



CAS433













LOCKS



Standard: Key lock



de Lock (optional padlock)



Padlockable Metallic Lock 1 (optional combination padlock)



Padlockable Metallic Lock 2 (optional combination padlock)



Metal handle



(coin-return)

MODEL

CAS431

CAS432

CAS433



Coin Collect Box (cash box, non coin-return)



Lock of 4 manuals digits with emergency key

OPTIONS



Mailbox Slot



Numeration plate



Nylon bracelet



Elastic bracelet


INTERIOR MEASUREMENTS (mm)

HEIGHT	WIDTH	DEPTH
318	278	318
318	278	318
458	228	418

COMBINATIONS AND DIMENSIONS



CAS431 COD: **35431 4**kg · **0,031**m³



CAS432 COD: **35432 7**kg · **0,058**m³



CAS433COD: 35433
10kg · 0,085m³